

SIRIUS

ANTARES

1.36 g/h **EFFICIENCY** 75.6%

TEST STANDARDS ULC S627

UL 1482 EPA 2020 NSPS





SIRIUS | ANTARES

Recommended surface (sq. ft) Exterior dimensions Exterior dimension with pedestal storage Opening dimension of pedestal storage Firebox dimensions Door opening Evacuation pipe Floor to ceiling clearance Maximum heat output (dry cordwood) Maximum heat output (test wood) Minimum heat output (test wood) Weight Sirius Weight Antares Log length (lateral)

Back evacuation pipe clearance Lateral clearance Corner clearance Efficiency Firebox capacity Outdoor air intake

MOBILE HOME APPROVED

26-7/8" W X 33" H X 25-1/2" D 41-3/8" H 13-5/8" W X 10" H 18-3/8" W X 10-7/8" H X 15-3/4" D 15-5/8" W X 9-1/8" H 84"

70,000 BTU 27,214 BTU/h 11,440 BTU/h 266 lbs 297 lbs 18" 10" 20"

75.6%

1.83 ft3

500 - 1,800

COLOR Metallic black

- Chrome-plated cast iron legs
- · Chrome-plated trim door
- Black enameled cast iron cooking plate
 2 blowers (150 CFM)
 and 1 thermodisc kit (VENT)
 (included with ANTARES)



LIMITED LIFETIME WARRANTY

DISTRIBUTED BY: