

ROBY 2500 CUISINIERE HIGH EFFICIENCY

1.3 g/h **EFFICIENCY** 78.6%

TEST STANDARDS CSA B415.1

ULC S627 UL 1482



HE PLUS

The **PLUS** was designed to be used with the ROBY 2500 to enhance comfort in the home. It's about a unique system of recovery heat that increase the calorific value. Using one or two blowers (460 to 920 CFM), the PLUS distributes heat more efficiently and increases stove efficiency by 40%.







TREAT YOURSELF WITH PEACE OF MIND WITH THIS DEVICE PROVIDING 95,000 BTU AND EQUIPPED WITH A FOOD WARMER AND CAST IRON COOKING PLATE. MOBILE HOME APPROVED.

ROBY 2500

Optimum efficiency Recommended surface (sq. ft) Exterior dimensions (without food warmer) Interior dimensions Door opening Evacuation pipe Floor to ceiling clearance Average capacity (dry cordwood) Average capacity (test wood) Weight Log length Back clearance Lateral and corner clearance Firebox capacity

78.6% 1,000 - 2,500 27-3/4" W X 33-1/8" H X 30-1/2" D 19" W X 10-7/8" H X 20" D 15-3/4" W X 10-1/4" H 84" 95.000 BTU 53,935 BTU/h 380 lbs 19" 12' 18" 2.87 ft³

Metallic black

ROBY 2500 CUISINIERE

Optimum efficiency 88% Recommended surface (sq. ft) 1,000 - 2,500 Exterior dimensions (with food warmer) 27-3/4" W X 54" H X 30-1/2" D Interior dimensions 19" W X 10-7/8" H X 20" D 15-3/4" W X 10-1/4" H Door opening Evacuation pipe Floor to ceiling clearance 84" 95.000 BTU Average capacity (dry cordwood) 53,935 BTU/h Average capacity (test wood) 440 lbs Weight Log length 19" Back clearance 12" 18" Lateral and corner clearance 2.87 ft³ Firebox capacity Metallic black Black enameled cast iron cooking plate included with ROBY 2500 CUISINIERE



- Chrome-plated cast iron legs
- Chrome-plated trim door
- Black enameled cast iron cooking plate: PLAQUECUID 2 blowers (150 CFM) and 1 thermodisc kit (VENT)
- Heat accumulator includes blower 460 CFM
- and thermodisc (PLUS)

 Additionnal 460 CFM for use with PLUS option (VENT460T+)
- MOBILE HOME APPROVED

(with option outdoor air intake TCPAE, to be installed in plant)

- Chrome-plated cast iron legs
- Chrome-plated trim door
- Small decorative chrome-plated top with mirror (TDDCHP)
 2 blowers (150 CFM) and 1 thermodisc kit (VENT)

(with option outdoor air intake TCPAE, to be installed in plant)

- MOBILE HOME APPROVED

24-1/2" W X 10" H X 12" D Door opening: 17-1/2" W X 6" H

DISTRIBUTED BY