

ULTIMATE 2015 HIGH EFFICIENCY COMBUSTION

HEATING BY CONVECTION AND RADIATION

2.4 g/h **EFFICIENCY** 78%

TEST STANDARDS

CSA B415.1 **ULC S627** UL 1482

HUGE **FIREBOX** 4.7 ft3



WHAT IS THE VENTULT

The **VENTULT** was designed to be used with the ULTIMATE 2015 to enhance comfort in the home. It is provided with an adaptor of two 6" ducts, a 460 CFM blower and a thermodisc kit which, when installed on top of ULTIMATE 2015, allows a better heat distribution in a large room or an open area or even to transfer heat to the upper floor via a grid floor or stairwell.



THE ULTIMATE 2015 IS PROVIDED WITH A HUGE FIREBOX WHICH ACCEPTS 25" LOG LENGTH AND HAS A HEATING CAPACITY UP TO 120,000 BTU. COMBINED WITH VENTULT (OPTIONAL), IT ALLOWS A BETTER HEAT DISTRIBUTION IN ANOTHER ROOM OR TO TRANSFER TO THE UPPER FLOOR.

ULTIMATE 2015

VENTULT

Recommended surface (sq. ft) 29" W X 37-13/16" H X 37-7/16" D 20-1/2" W X 15-1/2" H X 25-1/4" D Exterior dimensions Interior dimensions 16" W X 9-1/2" H Door opening Evacuation pipe Floor to ceiling clearance 120,000 BTU Average capacity (dry cordwood) 71.6% (dry cordwood 78%) Average capacity (test wood) Weight Log length 25" Back clearance Lateral and corner clearance 20" Firebox capacity 4.7 ft³ Metallic black



Adaptor of two 6" ducts, 460 CFM blower and thermodisc kit (VENTULT)
2 blowers (150 CFM) and 1 thermodisc kit (VENT)

DISTRIBUTED BY: